

XPS-220XP

10/100TX to 100FX SM/MM F/O PoE Media Converter



- 10/100BaseTX
- 100BaseFX SM/MM
- Total PoE Budget: 30 W
- IEEE802.3af/at
- Auto MDI/MDIX
- IEEE802.3x, Flow Control
- LFPT

Technical Specs.

Model No	XPS-220XP
Port Types	1 port RJ45 copper PoE ports + 1 Fiber SC Port

Performance

Wavelength	1310-1550 nm
Fiber Bandwidth	200 Mbps

Features

IEEE 802.3i	Auto Negotiation
IEEE 802.3u	IEEE 802.3af
Store and Forward	IEEE 802.3at
Link Fault Pass Through	IEEE 802.3x

Environment

DC Power Input	47-55V
Power Consumption	35W
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Humidity	10% - 90%, non-condensing

Mechanical

Dimension	116 x 99 x 25.5 mm
Weight	0.65 kg
Installation	Free-standing, wall mounted

Standards and Protocols

CE mark, commercial	VCCI Class B
FCC Part 15 Class B	EN 55022 (CISPR 22), Class B
CE/LVD EN60950	ISO 9001

Ordering Information

XPS-220MP	10/100TX to 100FX MM F/O PoE Media Converter
XPS-220SP	10/100TX to 100FX SM 20Km F/O PoE Media Converter