

## XPS-I7120-14P

10 port 10/100/1000T (8 ports PoE) + 4 port 100/1000 SFP L2+ Managed Industrial Switch



- 10 Port 1000BaseT
- 4 Port 100/1000 SFP
- L2+ Features
- Total PoE Budget: 240 W
- 8 ports PoE
- IEEE802.1x
- IEEE802.3az
- IEEE802.3z/ab
- IP30
- DIN Rail

### Technical Specs.

Model No	XPS-I7120-14P
Port Capacity	14 Port Gigabit Industrial Managed PoE Switch
Port Types	10x 10/100/1000Base-T RJ45 copper ports (8 ports PoE) + 2x 100/1000 SFP ports + 1 RJ45 console port

### Performance

Switching Capacity	28 Gbps , wire speed (non-blocking)
Forwarding Rate	20.83 Mpps
MAC Table	8K
Jumbo Frames	9.6K
Memory	4M
Auto-negotiation	•
Auto MDI/MDIX	•
Store-and-Forward	•

### Layer 2+ Features

Spanning Tree Protocol (STP)	IEEE802.1d Spanning Tree Protocol IEEE802.1w Rapid Spanning Tree Protocol IEEE802.1s Multiple Spanning Tree Protocol Loop Back Detection
IGMP Snooping	IGMP v1/v2
VLANs	Support up to 4K VLANs Port-based VLAN 802.1Q tag-based VLAN
Link Aggregation	IEEE 802.3ad LACP
Ethernet Ring Protection Switching	G.8032 ERPS
Flow Control	IEEE802.3x
Private VLAN	•
Static Routing	•
Q in Q	•

### Security Features

<p><b>Broadcast, multicast , unicast storm control</b>  <b>Secure Sockets Layer (SSL), Web security</b>  <b>DHCP Snooping</b>  <b>ARP Inspection</b>  <b>IP Source Guard</b>  <b>AAA, RADIUS and TACACS+</b></p>	<p><b>Secure Shell (SSH), Telnet security, supports SSH v1 and v2</b>  <b>ACL, VLAN ID or IP address,</b>  <b>MAC Based, Protocol based, Port Based, TCP/ UDP</b>  <b>Ethernet type,ICMP, IGMP, TCP flag</b>  <b>Port Security</b></p>
--	--

### Management

Web/SSL	SNMP	Firmware upgrade,
Port Mirroring	DHCP Client	(HTTP/HTTPs and TFTP)
Port Isolation	Web GUI Interface	LLDP
Telnet/SSH	Cable Diagnostics	SNTP
Ping	CPU Load	TFTP
HTTP/HTTPs	Dual Image	Syslog
Timezone	RMON	

### IPv6

IPv6 MLD snooping	IPv4/IPv6 Dual Protocol Stack
IPv6 Ping	

### Quality of Service

<b>CoS</b>	8 queues per port TCP/ UDP Strict priority Weighted Round Robin (WRR)
<b>Rate Limiting</b>	Ingress/Egress Rate control
<b>Traffic classification</b>	IEEE802.1p DSCP / IP precedence

### PoE

<b>Standard</b>	IEEE802.3af IEEE802.3at
<b>Total PoE Budget</b>	240W
<b>Max. PoE Power for each port</b>	30W
<b>Ports</b>	8 ports support PoE

### Environment

DC Power Input	47-55V
Total Power Consumption	254W
Operating/Storage Temperature	-40 - 75 °C / -50 - 85 °C
Operating Humidity	5% - 95% , non-condensing

### Mechanical

Dimension	165 x 148 x 54 mm
Weight	1.0 kg
Installation	IP30 rating , DIN-rail

### Standards

EN55022	EN61000-6-2	EN61000-4-5	IEC60068-2-27 Ea
EN61000-6-4	EN61000-4-2	EN61000-4-6	CE
EN61000-3-2	EN61000-4-3	EN61000-4-8	FCC
EN61000-3-3	EN61000-4-4	IEC60068-2-6	ISO 9001

### Ordering Information

<b>XPS-I7120-14P</b>	10 port 10/100/1000T (8 ports PoE) + 4 port 100/1000 SFP L2+ Managed Industrial Switch
----------------------	--

### Modules

<b>XPS-I21LX</b>	XPS Industrial Dual Core LX SM 10Km SFP Module -40/75°C
<b>XPS-I21SX</b>	XPS Industrial Dual Core SX MM SFP Module -40/75°C

\*more module ranges are available upon request.