

XPS-1200-18P

16 Port 10/100/1000 PoE + 2 Port 100/1000 SFP Unmanaged PoE Switch



- 16 Port 10/100/1000 PoE
- 2 100/1000 SFP
- Total PoE Budget: 250W
- IEEE802.3x

Technical Specs.

Model No	XPS-1200-18P
Port Capacity	18 Port Unmanaged PoE Switch
Port Types	16 port 10/100/1000Base-T RJ45 copper ports (PoE) + 2 port 100/1000 SFP

Performance

Switching Capacity	36 Gbps, wire speed, (non-blocking)
Forwarding Rate	26.78 Mpps
MAC Table	8K

Features

IEEE 802.3	IEEE 802.3z	IEEE 802.3af
IEEE 802.3i	IEEE 802.3ab	Auto MDI/MDIX
IEEE 802.3u	IEEE 802.3x	Auto Negotiation
Switch Architecture, Store-and-Forward		

PoE

Standard	IEEE802.3af
Total PoE Budget	250W
Max. PoE Power for each port	15.4W

Environment

Input Power	AC100-240V 50-60Hz
Total Power Consumption	266 W
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Operating Humidity	10% - 90%, non-condensing

Mechanical

Dimension	440 x 275 x 44.5 mm
Weight	3.415 kg

Standards and Protocols

CE Marks, commercial	EN 55022 (CISPR 22), Class B
EN 55022 (CISPR 22), Class B	CE/LVD EN60950
VCCI Class B	ISO 9001

Ordering Information

XPS-1200-18P	16 Port 10/100/1000 PoE + 2 Port 100/1000 SFP Unmanaged PoE Switch
---------------------	--

Modules

XPS-21LX	XPS Dual Core LX SM 10Km SFP Module -10/50°C
XPS-21SX	XPS Dual Core SX MM SFP Module -10/50°C

*more module ranges are available upon request.