

## XPS-1100-10

8 port 10/100TX + 2 Gigabit Combo Unmanaged Switch



- 8 Port 10/100BaseTX
- 2 Gigabit Combo
- IEEE802.3x
- Auto Negotiation
- Store-and-Forward

### Technical Specs.

Model No	XPS-1100-10
Port Types	8 port 10/100Base-TX RJ45 copper ports + 2 Gigabit Combo (10/100/1000BaseT - 100/1000 SFP)

### Performance

Switching Capacity	5.6 Gbps
Forwarding Rate	4.17 Mpps
MAC Table	16K

### Features

IEEE 802.3	IEEE 802.3x
IEEE 802.3i	Auto MDI/MDIX
IEEE 802.3u	Auto Negotiation
IEEE 802.3ab	Store-and-Forward
IEEE 802.3z	

### Environment

Input Power	AC100-240V, 1A, 50-60Hz
Total Power Consumption	12 W
Operating/Storage Temperature	0 - 50 °C / -20 - 75 °C
Operating Humidity	10% - 90%, non-condensing

### Mechanical

Dimension	270 x 181 x 44.6 mm
Weight	1.62 kg
Installation	Free-standing, wall mounted

### Standards and Protocols

CE	RoHS
FCC	ISO 9001

### Ordering Information

<b>XPS-1100-10</b>	8 port 10/100TX + 2 Gigabit Combo Unmanaged Switch
--------------------	--

### Modules

<b>XPS-21LX</b>	XPS Dual Core LX SM 10Km SFP Module -10/50°C
<b>XPS-21SX</b>	XPS Dual Core SX MM SFP Module -10/50°C

\*more module ranges are available upon request.