

XPS-I6100-10

8 port 10/100TX + 2 Gigabit Combo Unmanaged Industrial Switch



- 8 Port 10/100BaseTX
- 2 Gigabit Combo
- IEEE802.3x
- Auto Negotiation
- Store-and-Forward

Technical Specs.

Model No	XPS-I6100-10
Port Types	8 port 10/100Base-TX RJ45 copper ports + 2 Gigabit Combo (10/100/1000BaseT - 100/1000 SFP)

Performance

Switching Capacity	5.6 Gbps, wire speed (non-blocking)
Forwarding Rate	4.17 Mpps
MAC Table	16K

Features

IEEE 802.3	IEEE 802.3x
IEEE 802.3i	Auto MDI/MDIX
IEEE 802.3u	Auto Negotiation
IEEE 802.3ab	Store-and-Forward
IEEE 802.3z	

Environment

DC Power Input	12-48V
Total Power Consumption	9W
Operating/Storage Temperature	-40 - 75 °C / -50 - 85 °C
Operating Humidity	5% - 95% , non-condensing

Mechanical

Dimension	165 x 148 x 54 mm
Weight	0.90 kg
Installation	IP40 rating , DIN-rail

Standards and Protocols

EN55022	EN61000-6-2	EN61000-4-5	IEC60068-2-27 Ea
EN61000-6-4	EN61000-4-2	EN61000-4-6	CE
EN61000-3-2	EN61000-4-3	EN61000-4-8	FCC
EN61000-3-3	EN61000-4-4	IEC60068-2-6	ISO 9001

Ordering Information

XPS-I6100-10	8 port 10/100TX + 2 Gigabit Combo Unmanaged Industrial Switch
---------------------	---

Modules

XPS-I21LX	XPS Industrial Dual Core LX SM 10Km SFP Module -40/75°C
XPS-I21SX	XPS Industrial Dual Core SX MM SFP Module -40/75°C

*more module ranges are available upon request.